



CLEVEREVAC DYNAMIC GREEN EXIT SIGN



PRODUCT INFORMATION

Catalogue Number	DYGL-CP-RR
Description	L10 Optimum CleverEVAC Dynamic Green EXIT sign, with Volt Free (VF) & 24V Interface for ON/OFF Activation of Dynamic Green Enhancement.
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Ceiling / Wall Mounted Single Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing arrow activated on VF/24V input trigger and/or in emergency mode
Testing System	N/A - Manual test switch
Battery	Lithium Nanophosphate, 3.2V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Pictograph, Two elements (Running Man and Arrow Right) Dynamic LEDs sequencing along the Right Arrow when activated
Lamp(s)	LED panel, 60 x Duris E2, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	1.5 Watts (Standby), 5.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E1.25 C ₉₀ =B1.25 C ₉₀ =A1
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530030	BATTERY:L10 3.3V 2.5AH 260mm lead,noBRKT
8002920	PCA:CCF-Pro #CT10142-L8 CTP

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.

