



CLEVEREVAC DYNAMIC GREEN EXIT SIGN WITH SOUND ESCAPE



Dynamic LEDs Sequencing Arrow & Sounder activated

PRODUCT INFORMATION

Catalogue Number	DYGC-CP-SND-RR
Description	LP Premium CleverEVAC Dynamic Green EXIT sign, with Volt Free (VF) & 24V Interface for ON/OFF Activation of Dynamic Green Enhancement and Directional/Locatable Sounder (Sound Escape)
Construction	PC/ABS body with PC Diffuser
Mounting	Ceiling / Wall Mounted Single Sided
Dimensions L x W x H	446mm x 72mm x 214mm
Weight	2.4kg
Operating Mode	Maintained – Sequencing arrows & Sounder activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3200mAh Nickel Cadmium, 3.6V 600mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Pictograph, Two elements (Running Man and Arrow Right)
Lamp(s)	LED panel, 60 x Duris E2, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	4.0 Watts (Standby), 10 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E1.25 C ₉₀ =B1.25
Viewing Distance	24m

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
1510310	3xAA NiCad Battery Pk. 600mAh SBS.
8002925	PCA: DYxx Driver Board #CT10142-L8

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.

