

CLEVEREVAC DYNAMIC GREEN EXIT SIGN WITH SOUND ESCAPE



Dynamic LEDs Sequencing Inwards & Sounder Activated

PRODUCT INFORMATION

| | |
|-----------------------|--|
| Catalogue Number | DYGC-CP-SND-NC-R |
| Description | LP Premium CleverEVAC Dynamic Green EXIT sign, with Volt Free (VF) & 24V Interface for ON/OFF Activation of Dynamic Green Enhancement and Directional/Locatable Sounder (Sound Escape) |
| Construction | PC/ABS body with PC Diffuser |
| Mounting | Ceiling / Wall Mounted Single Sided |
| Dimensions L x W x H | 446mm x 72mm x 214mm |
| Weight | 2.4kg |
| Operating Mode | Maintained – Sequencing inward green LEDs & Sounder activated on opening of the VF/24V contact and capable of being activated in power-on and battery-backed mode |
| Testing System | N/A - Manual test switch |
| Battery | Lithium Iron Phosphate, 3.2V 3200mAh Nickel Cadmium, 3.6V 600mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Diffuser | Pictograph, Single element (Running Man) |
| Lamp(s) | LED panel, 60 x Duris, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 4.0 Watts (Standby), 10 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =E1.25 C ₉₀ =B1.25 C ₁₈₀ =B1.25 |
| Viewing Distance | 24m |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|---|
| 1550030 | BATT:LP 3.2V 3200mAh 260mm lead,noBRKT. |
| 1510310 | 3xAA NiCad Battery Pk. 600mAh SBS. |
| 8002925 | PCA: DYxx Driver Board #CT10142-L8 |

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.

